


SPECIFICATION OF SURFACE MOUNT TYPE

1 .TYPE	DSX321G				
2 .NOMINAL FREQUENCY	32.000000	MHz			
3 .LOAD CAPACITANCE(CL)	8.0	pF			
4 .DRIVE LEVEL	10	μW	+/-	2	μW
5 .FREQUENCY TOLERANCE	+/-	10	× 10 ⁻⁶	at 25 deg.C	+/- 3 deg.C
6 .SERIES RESISTANCE	50	ohms	max.	/	CL = SERIES
7 .FREQUENCY CHARACTERISTICS OVER TEMPERATURE(ref. +25 deg.C)	+/-	20	× 10 ⁻⁶	/	-40 deg.C to +85 deg.C
8 .OPERATING TEMPERATURE RANGE	-40	deg.C	to	+85	deg.C
9 .STORAGE TEMPERATURE RANGE	-40	deg.C	to	+85	deg.C
10 .SHUNT CAPACITANCE(C0)	2.0	pF	max.		
11 .INSULATION RESISTANCE	500 Mohms min. at 100V DC				
12 .OVERTONE ORDER	Fundamental				
13 .DIMENSIONS	Refer to Fig-1				
14 .PART NUMBER	257642				



(1)Logo, (2)Frequency and Manufacturing Location

Producing District	(1)Logo	(2)Frequency
INDONESIA	D	32
THAILAND	D	32
TAIWAN	D	<u>32</u>

- * Made in INDONESIA : Under Bar with (1)Logo
- * Made in THAILAND : Top Bar with (1)Logo
- * Made in TAIWAN : Under Bar with (2)Frequency

(3)Lot No.

unit : mm

Tolerance : +/-0.1

Pin #2 #4 is not connected with anything.

Fig.1