



P数	料号	U	V
1P	BS-C021	/	9.50
2P	BS-C022	10.00	19.50
3P	BS-C023	20.00	29.50
4P	BS-C024	30.00	39.50
5P	BS-C025	40.00	49.50
6P	BS-C026	50.00	59.50
7P	BS-C027	60.00	69.50
8P	BS-C028	70.00	79.50

Normal Geometric Tolerancing			
—	//	≡	⊥
0 to 100	0.2	0.3	0 to 10
over 100 to 150	0.3		over 10
over 150	0.5		0.3
Total Pitch Tolerances		Normal Dimension Tolerances	
0~30	±0.20	0~30	±0.25
over 30~53	±0.25	over 30~53	±0.30
over 53~70	±0.30	over 53~70	±0.35
over 70~90	±0.35	over 70~90	±0.44
over 90~115	±0.44	over 90~115	±0.55
over 115~150	±0.55	over 115~150	±0.70
over 150~200	±0.70	over 150~200	±0.85
over 200~250	±0.85	over 200~250	±1.00
over 250~320	±1.00	over 250~320	±1.20

NOTES:  
 1.RoHS Compliance  
 2.可根据客户需求,折成所需片数,各片数料号见表格

1	HOUSING	PA	UL94-V2 GRAY
ITEM	NAME OF PART	MATERIAL	NOTES

DWG.	ZW	DATE	2015.03.24	UNITS	MM	SHEET/OF	1 / 1
CHK.		DATE		SCALE	5:1 ( : )		
APP.		DATE		NAME	BS-C028		
DINKLE ENTERPRISE CO.,LTD				DWG NO.	SP-03-BSC02800		

△	REV.	CONTENT	NAME	DATE