



NOTES:

1. Rating: 150V 8A
2. Insulation Withstands Voltage:
AC 1600V at 1 minute
3. Insulation Resistance:
500MΩ or more at DC500V
4. Using Temperature Range:
-40°C ~ +105°C
5. RoHS Compliance

5	Partition Plate	PA	UL94-V2 GREY
4	End Stop(R)	PA	UL94-V2 GREY
3	End Stop(L)	PA	UL94-V2 GREY
2	Bus Terminal	COPPER ALLOY	Gold Plated
1	Plate Base	PA	UL94-V2 GREY
ITEM	NAME OF PART	MATERIAL	NOTES

Total Pitch Tolerances		Normal Dimension Tolerances	
0~30	±0.20	0~30	±0.25
over 30~53	±0.25	over 30~53	±0.30
over 53~70	±0.30	over 53~70	±0.35
over 70~90	±0.35	over 70~90	±0.44
over 90~115	±0.44	over 90~115	±0.55
over 115~150	±0.55	over 115~150	±0.70
over 150~200	±0.70	over 150~200	±0.85
over 200~250	±0.85	over 200~250	±1.00
over 250~320	±1.00	over 250~320	±1.20

DWG.	ZW	DATE	2016.07.08	UNITS	MM	SHEET/OF	1 / 1
CHK.		DATE		SCALE	3:1 (:)		
APP.		DATE		NAME	BS-020		
				DWG NO.	SP-03-BS020000		

REV.	CONTENT	NAME	DATE